

Dry Block Temperature Calibrator PYROS+

- Temperature range:
ambient temperature up to +600°C
- For mobile and stationary use
- Thermostat tests

Typical applications:

- Calibration and checking of all kind of thermometer
- Calibration and checking of thermostats

Technical Data:

Temperature range: ambient temperature up to +600°C
Accuracy of temperature reading: $\pm 0.6^\circ\text{C} \pm 1$ digit at 450°C
Display resolution: 0,1°C
Stability of regulated temperature: $\pm 0.15^\circ\text{C}$ at 450°C
Max. heating time: 20°C per minute
Max. cooling time: 25°C per minute
Ventilation: integrated, electronic regulated
Dry block: aluminum-bronze, diameter 50 mm
Test hole: 185 mm dept, with
insert with 4 holes (6.5 - 10.5 - 12.5 - 17 mm diam.)
Power supply: 230 VAC (optional: 115 VAC)
Power consumption: 800 VA

Case material: metall

Dimension: : 160 x 340 x 330 mm

Weight: 8 kg

NOTE: the stated accuracy is valid at ambient temperature +10°C...+40°C and is guaranteed for 1 year.



Scope of standard Supply:

- Temperature calibrator PYROS+
- Electr. power cable
- Fuses kit
- Electr. connection cables for thermostat tests
- Operating manual
- Certificate of calibration, traceable
- Tweezers for insert removing


Optional accessory Kit "KIT-Pyros+":

- Soft bag
- Insert without hole(s), to be drilled by customer
- Insert with 1 hole 9.5 mm diam.



Further optional accessory:

- Insert with drilling as per customers request



DRUCK & TEMPERATUR Leitenberger GmbH

Bahnhofstr. 33 • D-72138 Kirchentellinsfurt • Germany

Tel.: 0 71 21 - 9 09 20 - 0 • Fax: 0 71 21 - 9 09 20 - 99

E-Mail: DT-Info@Leitenberger.de • <http://www.druck-temperatur.de>

